








AC Axial Fan



Bearing type: ◎=Ball" B" ※=Sleeve" S" ○=1B1S "B(S)" ●=Hypro bearing" X"

PHOTO	Frame size (mm)	Model No.	Bearing Type B S B(S) X	Volt./Freq. (VAC/Hz)	Current (A)	Power (W)	Speed (rpm)	Maximum AirFlow		Maximum Pressure		Noise (dB/A)	Weight (g)
								(CMM)	(CFM)	(InAq)	(mmAq)		
	80x80x25	AA8251HB-AT	◎ † ○ -	115/50	0.15	17.30	2300	0.475	16.8	0.097	2.464	21.2	210
		AA8251MB-AT	◎ ※	115/60	0.13	14.90	2800	0.594	21.0	0.125	3.175	27.8	
		AA8252MB-AT	◎ ※	115/50	0.15	17.30	1900	0.413	14.6	0.060	1.500	18.3	
		AA8252MB-AT	◎ ※	230/50	0.07	16.10	1900	0.413	14.6	0.060	1.500	18.3	
				230/60	0.06	13.80	2500	0.535	18.9	0.110	2.750	24.0	
	80x80x38	AA8381HB-AT	◎ ※ ●	115/50	0.13	8.98	2300	0.679	24.0	0.110	2.812	25.3	320
		AA8381MS-AT	◎ ※ ●	115/60	0.10	6.75	2800	0.854	29.6	0.170	4.255	31.6	
		AA8381HX-AT	◎ ※ ●	115/50	0.08	5.42	2300	0.689	24.0	0.110	2.802	25.3	
		AA8381HX-AT	◎ ※ ●	115/60	0.07	4.61	2400	0.734	25.1	0.120	3.098	26.2	
		AA8381MX-AT	◎ ※ ●	115/50	0.13	8.98	2300	0.679	24.0	0.112	2.812	25.3	
		AA8381MX-AT	◎ ※ ●	115/60	0.10	6.75	2800	0.854	30.1	0.170	4.255	31.6	
		AA8382HS-AT	◎ ※ ●	230/50	0.07	8.80	2300	0.679	24.0	0.110	2.812	25.3	
		AA8382MS-AT	◎ ※ ●	230/60	0.06	6.80	2800	0.854	29.6	0.170	4.255	31.6	
				230/50	0.05	6.80	2300	0.687	24.0	0.110	2.802	25.3	
				230/60	0.05	5.70	2400	0.733	25.1	0.120	3.098	26.2	
	92x92x25	AA9252HB-AT	◎ ※	230/50	0.07	16.10	2000	0.792	28.0	0.066	1.676	24.1	230
		AA9252HB-AT	◎ ※	230/60	0.06	13.80	2400	0.962	34.0	0.094	2.388	30.1	
		AA9251MB-AT	◎ ※	115/50	0.15	17.30	1900	0.780	22.8	0.046	1.613	21.1	
		AA9251MB-AT	◎ ※	115/60	0.13	14.90	2150	0.894	29.1	0.073	1.955	26.8	
				230/50	0.07	16.10	1900	0.780	22.8	0.046	1.613	21.1	
				230/60	0.06	13.80	2150	0.894	29.1	0.073	1.955	26.8	
	120x120x25	AA1251MB-AT	◎ ※	115/50	0.22	23.00	2050	1.727	61.0	0.129	3.508	38.7	340
		AA1251MB-AT	◎ ※	115/60	0.19	19.60	2400	2.040	69.4	0.154	3.912	44.1	
		AA1252MB-AT	◎ ※	230/50	0.11	20.70	2050	1.727	61.0	0.129	3.508	38.7	
				230/60	0.10	18.40	2400	2.040	69.4	0.154	3.912	44.1	
	120x120x38.5	AA1281HB-AT	◎ ※ ●	115/50	0.25	16.30	2600	2.446	86.3	0.261	6.534	42.2	550
		AA1281HB-AT	◎ ※ ●	115/60	0.20	14.20	2900	2.721	96.1	0.231	5.779	44.5	
		AA1281MB-AT	◎ ※ ●	115/50	0.25	15.80	2500	2.268	80.0	0.211	5.280	40.0	
		AA1281MB-AT	◎ ※ ●	115/60	0.21	13.70	2700	2.450	86.5	0.169	4.238	41.0	
		AA1281LB-AT	◎ ※ ●	115/50	0.14	9.21	2400	2.142	75.6	0.170	4.273	40.1	
		AA1281LB-AT	◎ ※ ●	115/60	0.13	8.86	2100	1.887	66.6	0.083	2.088	37.9	
		AA1281DB-AT	◎ ※ ●	115/50	0.12	8.24	2300	2.117	74.7	0.139	3.478	39.2	
		AA1281DB-AT	◎ ※ ●	115/60	0.11	7.89	1650	1.481	52.3	0.057	1.426	30.5	
		AA1282HB-AT	◎ ※ ●	230/50	0.12	16.00	2600	2.446	86.3	0.261	6.534	42.2	
		AA1282HB-AT	◎ ※ ●	230/60	0.10	14.00	2900	2.721	96.1	0.231	5.779	44.5	
		AA1282MB-AT	◎ ※ ●	230/50	0.10	13.70	2500	2.268	80.0	0.211	5.280	40.0	
		AA1282MB-AT	◎ ※ ●	230/60	0.09	12.60	2700	2.450	86.5	0.169	4.238	41.0	
AA1282LB-AT	◎ ※ ●	230/50	0.07	9.90	2400	2.142	75.6	0.170	4.273	40.1			
AA1282LB-AT	◎ ※ ●	230/60	0.07	9.40	2100	1.887	66.6	0.083	2.088	37.9			
AA1282DB-AT	◎ ※ ●	230/50	0.06	8.00	2300	2.117	74.7	0.139	3.478	39.2			
				230/60	0.06	7.60	1650	1.481	52.3	0.057	1.426	30.5	

Specifications subject to change without notice.

6600 Park of Commerce Blvd. • Boca Raton, FL 33487 • 561-241-6700 Phone • 561-241-3328 Fax • www.jarothermal.com