








AC Axial Fan



Bearing type: ◎=Ball "B" ※=Sleeve "S" ○=1B1S "B(S)" ●=Hypro bearing "X"

PHOTO	Frame size (mm)	Model No.	Bearing Type B S B(S) X	Volt./Freq. (VAC/Hz)	Current (A)	Power (W)	Speed (rpm)	Maximum AirFlow		Maximum Pressure		Noise (dB/A)	Weight (g)
								(CMM)	(CFM)	(InAq)	(mmAq)		
	172x150x51	AK1651HB	◎	110-115/50	0.56	38	2600	5.400	190.0	0.630	16.00	50±2	1050
				110-115/60	0.50	36	3000	6.500	230.0	0.790	20.00	50±2	
		AK1651MB	◎	110-115/50	0.28	25	2300	4.500	159.0	0.510	13.00	40±2	
				110-115/60	0.27	23	2400	4.200	148.0	0.550	14.00	40±2	
		AK1651LB	◎	110-115/50	0.21	22	1600	3.200	113.0	0.400	10.00	32±2	
				110-115/60	0.19	20	1400	2.900	100.0	0.310	8.00	32±2	
		AK1652HB	◎	200-240/50	0.30	38	2600	5.400	190.0	0.630	16.00	50±2	
				200-240/60	0.25	36	3000	6.500	230.0	0.790	20.00	50±2	
	172x150x51	AK1751HB	◎	110-115/50	0.24	24	2600	5.400	190.0	0.630	16.00	50±2	1050
				110-115/60	0.25	28	3000	6.600	235.0	0.790	20.00	50±2	
		AK1751MB	◎	110-115/50	0.17	20	2470	4.700	165.0	0.510	13.00	40±2	
				110-115/60	0.21	23	2370	4.800	170.0	0.550	14.00	40±2	
		AK1751LB	◎	110-115/50	0.16	16	1600	3.100	110.0	0.400	10.00	32±2	
				110-115/60	0.20	18	1800	3.000	106.0	0.310	8.00	32±2	
		AK1752HB	◎	200-240/50	0.12	24	2600	5.400	190.0	0.630	16.00	50±2	
				200-240/60	0.16	28	3000	6.600	235.0	0.790	20.00	50±2	
	176x176x89	AK1781HB	◎	100-120/50	0.57	50	2650	10.800	380.0	0.790	20.00	60±2	1800
				100-120/60	0.48	52	3200	13.000	450.0	1.020	26.00	60±2	
		AK1782HB	◎	200-240/50	0.21	43	2650	10.800	380.0	0.790	20.00	60±2	
				200-240/60	0.23	52	3200	13.000	450.0	1.020	26.00	60±2	
	180x180x65	AK1861HB	◎	100-120/50	0.53	50	2650	10.800	380.0	0.790	20.00	60±2	1800
				100-120/60	0.50	52	3200	13.000	450.0	1.020	26.00	60±2	
		AK1862HB	◎	200-240/50	0.23	43	2650	10.800	380.0	0.790	20.00	60±2	
				200-240/60	0.24	52	3200	13.000	450.0	1.020	26.00	60±2	
	205x205x72	AK2071HB	◎	110/50	0.60	65	2800	16.40	580.0	0.980	25.00	60±2	2100
				110/60	1.00	102	3000	18.30	647.0	1.100	28.00	60±2	
		AK2072HB	◎	220/50	0.30	65	2800	16.40	580.0	0.980	25.00	60±2	
				220/60	0.49	102	3000	18.30	647.0	1.100	28.00	60±2	
	254x89	AK2581HB	◎	100-115/50	0.55	60	2150	24.50	867.0	0.460	11.70	56±2	2000
				100-115/60	0.62	67	2000	22.80	806.0	0.370	9.40	56±2	
		AK2581MB	◎	100-115/50	0.22	34	1400	17.00	600.0	0.270	6.90	51±2	
				100-115/60	0.24	37	1600	18.80	665.0	0.360	9.10	51±2	
		AK2582HB	◎	220-240/50	0.26	60	2300	25.90	915.0	0.490	12.40	58±2	
				220-240/60	0.30	67	2200	25.10	886.0	0.410	10.40	58±2	
		AK2582MB	◎	200-240/50	0.16	34	1400	17.00	600.0	0.270	6.90	51±2	
				200-240/60	0.14	37	1600	18.80	665.0	0.360	9.10	51±2	

Specifications subject to change without notice.