


DC Blower



Bearing type: ⊙=Ball "B" ※=Sleeve "S" ○=1B1S "B(S)" ●=Hypro bearing "X"

PHOTO	Frame size (mm)	Model No.	Bearing Type B S B(S) X			Voltage (v)	Current (A)	Power (W)	Speed (rpm)	Maximum AirFlow		Maximum Pressure		Noise (dB/A)	Weight (g)
			B	S	B(S)					X	(CMM)	(CFM)	(InAq)		
	30x30x10	AB0305MX-GA0	⊙	○	●	5	0.15	0.75	7500	0.028	0.98	0.176	4.41	28.0	12
		AB0305HX-GA0	⊙	○	●	5	0.20	1.00	9000	0.034	1.20	0.263	6.59	33.0	
		AB0312MB-GA0	⊙	○	●	12	0.09	0.96	7500	0.028	0.98	0.176	4.41	28.0	
		AB0312HB-GA0	⊙	○	●	12	0.10	1.20	9000	0.034	1.20	0.263	6.59	33.0	
		AB0305MX-GA6	⊙	○	●	5	0.15	0.75	7500	0.028	0.98	0.176	4.41	28.0	
		AB0305HX-GA6	⊙	○	●	5	0.20	1.00	9000	0.034	1.20	0.263	6.59	33.0	
		AB0312MB-GA6	⊙	○	●	12	0.09	0.96	7500	0.028	0.98	0.176	4.41	28.0	
		AB0312HB-GA6	⊙	○	●	12	0.10	1.20	9000	0.034	1.20	0.263	6.59	33.0	
	35x35x07	AB3505LX-QB0		○	●	5	0.10	0.50	5500	0.003	0.09	0.126	3.20	19.0	13
		AB3505MX-QB0		○	●	5	0.14	0.70	6500	0.031	1.11	0.192	4.79	23.0	
		AB3505HX-QB0		○	●	5	0.23	1.15	7500	0.038	1.33	0.260	6.51	28.3	
		AB3512MX-QB0		○	●	12	0.12	0.14	6500	0.031	1.11	0.192	4.79	23.0	
	35x35x10	AB3505LB-GA0	⊙	○		5	0.09	0.45	5000	0.026	0.91	0.042	1.05	23.0	16
		AB3505MX-GA0	⊙	○	●	5	0.11	0.55	6000	0.035	1.22	0.153	3.84	27.5	
		AB3505HX-GA0	⊙	○	●	5	0.17	0.85	7000	0.043	1.52	0.199	4.98	30.7	
		AB3512LX-GA0		○	●	12	0.11	0.13	5000	0.026	0.91	0.042	1.05	23.0	
		AB3512MB-GA0	⊙	○	●	12	0.09	0.11	6000	0.035	1.22	0.153	3.84	27.5	
		AB3512HB-GA0	⊙	○		12	0.10	0.12	7000	0.043	1.52	0.199	4.98	30.7	
	45x45x07	AB4505LB-QA0(S)		○		5	0.07	0.35	4700	0.042	1.50	0.202	5.13	23.3	23
		AB4505MB-QA0(S)		○		5	0.11	0.55	5500	0.048	1.70	0.289	7.33	27.9	
		AB4505HB-QA0(S)		○		5	0.14	0.70	6200	0.059	2.10	0.391	9.93	31.2	
		AB4505LX-QA0			●	5	0.07	0.35	4300	0.039	1.37	0.163	4.13	20.8	
		AB4505MX-QA0			●	5	0.11	0.55	5000	0.044	1.56	0.230	5.83	25.8	
		AB4505HX-QA0			●	5	0.14	0.70	5700	0.052	1.83	0.320	8.14	28.7	
		AB4512LB-QA0(S)		○		12	0.08	0.96	4700	0.042	1.50	0.202	5.13	23.3	
		AB4512MB-QA0(S)		○		12	0.09	1.08	5500	0.048	1.70	0.289	7.33	27.9	
		AB4512HB-QA0(S)		○		12	0.10	1.20	6200	0.059	2.10	0.391	9.93	31.2	
	45x45x10	AB4505MB-GD1(B)	⊙	※	●	5	0.15	0.75	5000	0.065	2.31	0.348	8.69	31.1	25
		AB4505LB-GD1(B)	⊙	※	●	5	0.13	0.30	4000	0.051	1.80	0.221	5.53	24.5	

Specifications subject to change without notice.

