


DC Chip Cooler



Bearing type: ○=Ball"B" ※=Sleeve"S" ◯=1B1S"B(S)" ●=Hypro bearing"X"

PHOTO	Frame size (mm)	Model No.	Bearing Type B S B(S) X	Voltage (VDC)	Current (A)	Power (W)	Speed (rpm)	Maximum AirFlow (CMM)	Maximum AirFlow (CFM)	Maximum Pressure (InAq)	Maximum Pressure (mmAq)	Noise (dB/A)	Weight (g)
	35x35x08	AP3505LX-J70	○ ●	5	0.09	0.45	7500	0.071	2.50	0.082	2.05	20.0	6
		AP3505MX-J70	○ ●	5	0.12	0.60	9000	0.093	3.30	0.138	3.45	27.9	
		AP3505HX-J70	○ ●	5	0.18	0.90	10500	0.116	4.10	0.151	3.78	32.0	
		AP3512LX-J70	○ ●	12	0.06	0.72	7500	0.071	2.50	0.082	2.05	20.0	
		AP3512MX-J70	○ ●	12	0.10	0.52	9000	0.093	3.30	0.138	3.45	27.9	
		AP3512HX-J70	○ ●	12	0.08	0.96	10500	0.116	4.10	0.151	3.78	32.0	
	40x40x08	AP0405MX-J70	●	5	0.14	0.70	7000	0.133	4.70	0.111	2.78	28.0	15
		AP0405MX-J73	○ ●	5	0.10	0.50	7000	0.133	4.70	0.111	2.78	28.0	
		AP0405HX-J73	○ ●	5	0.13	0.65	8000	0.139	4.90	0.111	2.78	28.0	
		AP0412MX-J70	○ ●	12	0.08	0.96	7000	0.133	4.70	0.150	3.75	35.0	
	40x40x10	AP0405MX-G70	●	5	0.14	0.70	8000	0.133	4.70	0.111	2.78	28.0	19.2
		AP0405HX-G73	●	5	0.13	0.65	9000	0.139	4.90	0.150	3.75	35.0	
		AP0412LX-G70	●	12	0.07	0.84	6500	0.099	3.50	0.063	1.58	19.0	
		AP0412MX-G70	○ ●	12	0.08	0.96	8000	0.133	4.70	0.111	2.78	28.0	
	45x45x08	AP4505HB-J90	○ ●	5	0.12	0.60	6200	0.171	6.00	0.090	2.29	30.0	18
		AP4505MB-J90	○ ●	5	0.09	0.45	5500	0.148	5.20	0.064	1.63	23.8	
		AP4505LB-J90	○ ●	5	0.07	0.35	4500	0.120	4.20	0.044	1.12	19.5	
		AP4512HB-J90	○ ●	12	0.08	0.96	6200	0.171	6.00	0.090	2.29	30.0	
		AP4512MB-J90	○ ●	12	0.06	0.72	5500	0.148	5.20	0.064	1.63	23.8	
		AP4512LB-J90	○ ●	12	0.06	0.72	4500	0.120	4.20	0.044	1.12	19.5	
	45x45x10	AP4505HB-G90	※ ●	5	0.12	0.60	6200	0.171	6.00	0.09	2.29	30.0	18
		AP4505MB-G90	※ ●	5	0.09	0.45	5800	0.157	5.50	0.067	1.70	25.0	
		AP4505LB-G90	※ ●	5	0.05	0.25	4800	0.128	4.50	0.051	1.30	19.9	
		AP4512HB-G90	※ ●	12	0.08	0.96	6200	0.171	6.00	0.09	2.29	30.0	
		AP4512MB-G90	※ ●	12	0.06	0.72	5800	0.157	5.50	0.067	1.70	25.0	
		AP4512LB-G90	※ ●	12	0.06	0.72	4800	0.128	4.50	0.051	1.30	19.9	
	50x50x08	AP0505LX-J90	●	5	0.1	0.50	4300	0.175	6.20	0.079	1.98	23.0	29
		AP0505MX-J90	●	5	0.12	0.60	5000	0.201	7.10	0.105	2.62	25.5	
		AP0505HX-J90	●	5	0.14	0.70	6300	0.260	9.20	0.146	3.64	32.6	
		AP0512LX-J90	●	12	0.08	0.96	4300	0.175	6.20	0.079	1.98	23.0	
		AP0512MX-J90	●	12	0.09	1.08	5000	0.201	7.10	0.105	2.62	25.5	
		AP0512HX-J90	●	12	0.1	1.20	6300	0.260	9.20	0.146	3.65	32.6	
		AP0505LB-J90(S)	○	5	0.1	0.50	4500	0.184	6.50	0.084	2.09	23.3	
		AP0505MB-J90(S)	○	5	0.12	0.60	5500	0.204	7.20	0.120	3.00	26.5	
		AP0505HB-J90(S)	○	5	0.14	0.70	6600	0.269	9.50	0.157	3.92	33.0	
		AP0512LB-J90(S)	○	12	0.08	0.96	4500	0.184	6.50	0.084	2.09	23.3	
		AP0512MB-J90(S)	○	12	0.09	1.08	5500	0.204	7.20	0.120	3.00	26.5	
AP0512HB-J90(S)	○	12	0.1	1.20	6600	0.269	9.50	0.157	3.92	33.0			
	52x52x12	AP5212MX-E70(8)	●	12	0.07	0.84	4300	0.297	10.50	0.100			24.5

Specifications subject to change without notice.

